

LinkBridge™ Fiber Optic Extender Transmitter Wall Plate And Receiver Kit



18G/4K HDMI Transmitter 1 Multimode Receiver HDMI Ouput

Overview

The LBO-H2P Series is a high performance, low cost, small form-factor, Fiber Optic 18G/4K HDMI Transmission System (Transmitter and Receiver). It carries one (1) unidirectional 18G/4K HDMI video signal that supports all HDR formats, including HDR10+ and Dolby Digital along with HDCP/DDC support, over one (1) multimode fiber cable. Provides fully uncompressed video without any color space conversion and audio extension with zero loss of quality. This unique fiber optic transmission system lets your digital flat panel display extend up to 300m at 4k@60Hz, 4:4:4 resolution.

Features

- Extend 18G/4K HDMI signals up to 300 meters over OM3 multimode fiber
- Video Resolutions up to 4K (18 Gbps) @ 60Hz, 4:4:4
- Fully uncompressed video and audio provides zero loss of quality
- Video over 1 multimode fiber
- HDCP 1.4 and 2.2/2.3 compliant
- Multi color status LED (6 mode indicator LEDs)
- 1 GANG wall plate



LinkBridge™ Fiber Optic Extender Transmitter Wall Plate And Receiver Kit

VIDEO SPECIFICATIONS

Resolution Up to 4K @ 60Hz. 4:4:4

HDMI Connector

Protocol DDC/HDCP 2.2, HDR

USB POWER

Fiber Type Multimode

Number of Fibers 1 Connector SC

PHYSICAL

Dimensions 1.8" (W) x 2.8" (D) x 4.1" (H) Tx

1.4" (W) x 2.5" (D) x 0.6 (H) Rx

Power Consumption 12V DC @ 200mA Tx

5V DC @ 500mA (max) Rx

LED Indicator Power/Link/HDCP

0 to 40°C **Operating Temperature Storage Temperature** -10 to 60°C

Humidity 0 to 95% RH, Non-Condensing

CERTIFICATION

CE, FCC, 60601-1

COMPLIANCE

ROHS, REACH

ORDER INFORMATION

LBO-H2P-T/R-WP KIT Fiber Optic 18G/4K HDMI 1 GANG

Style wall plate Transmitter, Decora, and Receiver Module

Multimode, 1-Fiber

PANEL DRAWING





